

CHI MEI CORPORATION

59-1 SAN CHIA JEN TE TAINAN HSIEN TAIWAN

Material Designation: **PA-764 (+)**

Product Description: Acrylonitrile Butadiene Styrene (ABS), designated "Polylac" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	V-0, 5VB	1	0	75	85	75	-	-
	2.5	5VA	-	-	75	85	75	-	-
	3.0	V-0	0	0	85	85	85	-	-
CTI: 2	IEC CTI: -	HVTR: 0	D495: 7					IEC Ball Pressure (°C): -	
Dielectric Strength (kV/mm): - ISO Tensile Strength (MPa): - ISO Tensile Impact (kJ/m²): -		Dimensional Stability(%): -							
		ISO Heat Deflection (°C): -							
		ISO Charpy Impact (kJ/m²): -							
		Volume Resistivity (10*ohm-cm): -							
		ISO Flexural Strength (MPa): -							
		ISO Izod Impact (kJ/m²): -							

(+) Optional prefix or suffix may be used to denote 0-0.5% acid scavengers.

Report Date: 6/23/1983

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.