

CHI MEI CORPORATION

59-1 SAN CHIA JEN TE TAINAN HSIEN TAIWAN

Material Designation: **PA-765B (+)**

Product Description: Acrylonitrile Butadiene Styrene (ABS), designated "Polylac" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	V-2	4	0	80	80	65	-	-
	2.1	V-2	2	0	80	80	65	-	-
	2.5	V-0, 5VB	2	0	80	80	65	-	-
	3.0	V-0, 5VA	2	0	80	80	75	-	-
CTI: 0	IEC CTI: -	HVTR: 2			D495: 7			IEC Ball Pressure (°C): -	
Dielectric Strength (kV/mm): -					Volume Resistivity (10⁹ohm-cm): -			Dimensional Stability(%): -	
ISO Tensile Strength (MPa): -					ISO Flexural Strength (MPa): -			ISO Heat Deflection (°C): -	
ISO Tensile Impact (kJ/m²): -					ISO Izod Impact (kJ/m²): -			ISO Charpy Impact (kJ/m²): -	

(+)
Optional prefix or suffix may be used to denote 0-0.5% acid scavengers.

Report Date: 6/23/1983

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.