

CHI MEI CORPORATION

59-1 SAN CHIA JEN TE TAINAN HSIEN TAIWAN

Material Designation: **PA-756H**

Product Description: Acrylonitrile Butadiene Styrene (ABS), designated "Polylac" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	HB	4	0	60	60	60	-	-
	3.0	HB	3	0	60	60	60	-	-
CTI: 0	IEC CTI: -	HVTR: 0	D495: 6					IEC Ball Pressure (°C): -	
Dielectric Strength (kV/mm): - ISO Tensile Strength (MPa): - ISO Tensile Impact (kJ/m²): -		Volume Resistivity (10×ohm-cm): - ISO Flexural Strength (MPa): - ISO Izod Impact (kJ/m²): -						Dimensional Stability(%) : -	
								ISO Heat Deflection (°C): -	
								ISO Charpy Impact (kJ/m²): -	

Report Date: 6/23/1983

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.